LOEGERING



Adjustable Forks

Heavy-Duty Guard Plate

Universal Mounting System

Convenient Entry Steps

Multiple Fork Lengths

Custom Naming Feature Option

When performance counts... Count on Loegering.

Constructed of rugged, heavy-gauge steel, Loegering pallet forks are built to withstand the rigors of any job site. With performance that exceeds your expectations, this innovative attachment has the added value of operator ease and enhanced safety. Also, pallet fork productivity is maximized when used with Loegering tracks. Loegering. Not just a better pallet fork. A smarter pallet fork.

Features & Benefits

- Recessed forks prevent damage to pallets, boxes or other bulky materials.
- Adj ustable forks allow operators to adjust the spacing between fork tines from 9 to 45 inches.
- Heavy-duty guard plate prevents objects from sliding off while maintaining excellent visibility.
- Universal mounting system offers quick attachment to both old and new generation skid steers.
- Convenient entry steps allow operators easy access to the loader.
- Multiple fork lengths offer the flexibility to accommodate a variety of applications.
 - Custom naming feature option



Specifications

	PF42	PF42HD	PF48	PF48HD
Frame Width	46.5 in.	54.5 in.	46.5 in.	54.5 in.
Overall Width	57 in.	65 in.	57 in.	65 in.
Frame Height	36 in.	36 in.	36 in.	36 in.
Overall Height	39 ^{1/2} in.	39 ^{1/2} in.	39 ^{1/2} in.	39 ^{1/2} in.
Tine Length	42 in.	42 in.	48 in.	48 in.
Tine Thickness	1 ^{3/8} in.	1 ^{3/4} in.	1 ^{3/8} in.	1 ^{3/4} in.
Tine Width	4 in.	4 in.	4 in.	4 in.
Frame Weight	205 lbs.	254 lbs.	205 lbs.	254 lbs.
Total Weight	400 lbs.	485 lbs.	420 lbs.	500 lbs.
Load rating capacity	3,900 lbs. @ 24 in.	6,200 lbs. @ 24 in.	3,900 lbs. @ 24 in.	6,200 lbs. @ 24 in.



Casselton, ND 58012 800.373.5441 701.347.5441 Fax: 701.347.4323 www.loegering.com

Our mission: Be a steward of excellence by building on our foundation of quality products, customer service, profitability and ethical treatment of people.